

2X2 & 2X4 LENSED TROFFER






DESCRIPTION

The T Series of specification grade high performance luminaires are designed for general illumination in commercial, institutional, and retail lighting applications. The 4 1/2" deep, painted after fabrication (PAF), housing offers superior light performance and diffusion.

FEATURES

- Hot dipped galvanized uni-body construction with built-in tabs for structural integrity
- Specific body design for each lamp configuration, limiting holes for a streamlined design
- Oversized access plate for ease of installation
- PAF for consistent finish, safe handling, and corrosion resistance
- Baked white enamel provides a reflectance factor of 90% or greater
- Built in earthquake/hurricane clips
- NEMA type G (Grid) standard. NEMA type F (Flange) available for field installation.
- All lamps may be installed or removed in any order
- 3 3/16" lamp to lens for better light dispersion
- UL listed
- Suitable for damp locations
- All fixtures come with factory installed power disconnect
- All fixtures are 100% tested at the factory

LAMP CONFIGURATIONS



DIMENSIONS	L	W	H
2' x 4'	47 3/4"	23 15/16"	4 1/2"
2' x 2'	23 15/16"	23 15/16"	4 1/2"

2 x 2 & 2 x 4 Lensed Troffer Matrix - Sample part code: (Example: **T4432DLW**)

T	4	4	32	D	L	W		
SERIES	DIMENSIONS		LAMP WATTAGE	LAMPS		WHIP	OPTIONS	
T	2: 2 x 2 4: 2 x 4		2 x 2 Lamping 14: 14W T5 17: 17W T8 24: 24W T5HO ¹ 32: 32W U-T8 2 x 4 Lamping 28: 28W T5 32: 32W T8 54: 54W T5HO ¹	Blank: No Lamps L: Include Lamps* (Standard 741K)		Blank: No Whip W: Include Whip	Blank: No Options E: Emergency Ballast ² K: Dual Ballast F: Fused	
LAMP CONFIGURATIONS			VOLTAGE		LENS			
2: 2 Lamps 3: 3 Lamps 4: 4 Lamps 6: 6 Lamps			A: 120V D: 120-277V		Blank: .095 Lens G: .125 Lens H: .156 Lens J: Drop Lens U: 1/2" Egg Crate V: 1 1/4" Egg Crate			

¹T5HO are not available in 6 light version
²Consult factory for other available options