



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com



SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

DESCRIPTION:

BLS6ICNAT-N is a 6" aperture sloped housing for one vertical Incandescent lamp, UL, C-UL listed for damp location. The BLS6ICNAT-N is designed for insulated ceilings and can be in direct contact with insulation. It is thermally protected against misuse of insulation materials and improper lamping. This air-tight housing design prevents airflow through ceiling for saving heating and air conditioning costs. The BLS6ICNAT-N offers a choice of trim types including baffle, reflector, lensed and eyeball trims.

HOUSING/MOUNTING FRAME:

6", new work, air-tight installation. Mounting frame of galvanized steel is 7 1/2" W x 13" L. The housing adjusts for ceilings up to 1 1/4" thick. Adjustable socket mounting plate for proper positioning of different lamp types. Sloped housing accommodates ceilings at 2/12 to 6/12 pitch (approximately 10° to 30°).

BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. The bar hangers can be turned 90° on the plaster frame. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

LAMPING/SOCKET:

75W Max., 120V (Lamp wattage based on trim). Adjustable socket mounting plate for proper positioning of different lamp types.

JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

COMPLIANCE:

UL, C-UL listed for damp location.
Certified Air-Tight under ATM-E283

WARRANTY:


Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

ORDERING INFORMATION

BLS6ICNAT-N

Sample Part Code: BLS6ICNAT-N



SERIES

BLS6ICNAT-N: IC Rated, Air Tight Housing

BLS6ICNAT-N

6" Sloped IC Type Housing for New Work Line Voltage



SPECIFICATIONS



7 1/16" x 6 7/8"
Ceiling cut-out

