



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com



SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

DESCRIPTION:

BLV181CNAT-N is a 4" aperture housing for one vertical halogen lamp, UL, C-UL listed for damp location. The BLV181CNAT-N is designed for insulated ceilings and can be in direct contact with insulation. It is thermally protected against misuse of insulation materials and improper lamping. This air-tight housing design prevents airflow through ceiling for saving heating and air conditioning costs. The BLV181CNAT-N offers a choice of trim types including baffle, reflector, lensed and eyeball trims.

HOUSING/MOUNTING FRAME:

4", new work, air-tight installation. Mounting frame of galvanized steel is 13 1/4" L x 9 1/2" W. The housing adjusts for ceilings up to 1 1/4" thick

BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. The bar hangers can be turned 90° on the plaster frame. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

LAMPING/SOCKET:

50W Max., 12V MR-16 (Lamp wattage based on trim). Adjustable socket mounting plate for proper positioning of different lamp types. Uses 120V to 12V magnetic transformer

JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

COMPLIANCE:

UL, C-UL listed for damp location.
Certified Air-Tight under ATM-E283

WARRANTY:

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

BLV181CNAT-N


4" IC Type Housing for New Work Low Voltage



ORDERING INFORMATION

BLV181CNAT-N

Sample Part Code: BLV181CNAT-N



SERIES

BLV181CNAT-N: IC Rated, Air Tight Housing

SPECIFICATIONS

