



# TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986  
tel: (772) 878-4944 or on the web at [www.tamliteusa.com](http://www.tamliteusa.com)



## SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

### DESCRIPTION:

DL205 is a Non-IC rated, 5" aperture new work housing, for one vertical Incandescent lamp. UL, C-UL listed for damp location. The DL205 is thermally protected against misuse of insulation materials and improper lamping. Designed for use in non-insulated areas. If installed where insulation is present, the insulation must be pulled back 3" from all sides of the DL205 housing. The DL205 offers a choice of trim types including baffle, reflector, lensed and eyeball trims.

### HOUSING/MOUNTING FRAME:

This 5", new work, Mounting frame in galvanized steel 7 1/16" W x 10 3/8" L. The housing adjusts for ceilings up to 1 1/4" thick.

### BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. The bar hangers can be turned 90° on the plaster frame. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

### LAMPING/SOCKET:

75W Max., 120V (Lamp wattage based on trim). Adjustable socket mounting plate for proper positioning of different lamp types.

### JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

### COMPLIANCE:

UL, C-UL listed for damp location.

### WARRANTY:

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

\*\*\* SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE\*\*\*

### ORDERING INFORMATION

## DL205

Sample Part Code: DL205



SERIES

DL205: Non-IC Rated, Recessed Housing

# DL205

## 5" Non-IC Type Housing for New Work Line Voltage



### DIMENSIONS DATA

