



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com



SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

DESCRIPTION:

DL906 is a Non-IC rated 6" aperture sloped housing for one vertical Incandescent lamp, UL, C-UL listed for damp location. It is thermally protected against misuse of insulation materials and improper lamping. Design for use in non-insulated areas. If installed where insulation is present, the insulation must be pulled back 3" from all sides of the DL906 housing. The DL906 offers a choice of trim types including baffle, reflector, lensed and eyeball trims.

HOUSING/MOUNTING FRAME:

6", new work, Mounting frame of galvanized steel is 7 1/16" W x 12" L. The housing adjusts for ceilings up to 1 1/4" thick. Adjustable socket mounting plate for proper positioning of different lamp types. Sloped housing accommodates ceilings at 2/12 to 6/12 pitch (approximately 10° to 30°).

BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. The bar hangers can be turned 90° on the plaster frame. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

LAMPING/SOCKET:

150W Max., 120V (Lamp wattage based on trim). Adjustable socket mounting plate for proper positioning of different lamp types.

JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

COMPLIANCE:

UL, C-UL listed for damp location.

WARRANTY:


Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

ORDERING INFORMATION

DL906

Sample Part Code: DL906



SERIES

DL906: Non-IC Rated, Sloped Housing

DL906

6" Sloped Non-IC Type Housing for New Work Line Voltage



SPECIFICATIONS

