



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com



SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

DESCRIPTION:

DLH106 is a Non-IC rated, 6" aperture new work housing, for one MR-16 halogen lamp. UL, C-UL listed for damp location. The DLH106 is thermally protected against misuse of insulation materials and improper lamping. Design for use in non-insulated areas. If installed where insulation is present, the insulation must be pulled back 3" from all sides of the DLH106 housing. The DLH106 offers a choice of trim types including baffle and reflector trims.

HOUSING/MOUNTING FRAME:

This 6", new work, Mounting frame is made of galvanized steel - 7 1/16" W x 10 3/8" L. The housing adjusts for ceilings up to 1 1/4" thick.

BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. The bar hangers can be turned 90° on the plaster frame. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

LAMPING/SOCKET:

50W Max., 12V GU5.3 base MR-16 (Lamp wattage based on trim). Adjustable socket mounting plate for proper positioning of different lamp types. Uses 120V to 12V magnetic transformer.

JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

COMPLIANCE:

UL, C-UL listed for damp location.

WARRANTY:


Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

ORDERING INFORMATION

DLH106

Sample Part Code: DLH106



SERIES

DLH106: Non-IC Rated, Recessed Housing

DLH106

6" Non-IC Type Housing for New Work Line Voltage



DIMENSIONS DATA

