



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com



SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

DESCRIPTION:

IC206AT is a 6" aperture housing for one vertical Incandescent lamp, UL, C-UL listed for damp location. The IC206AT is designed for insulated ceilings and can be in direct contact with insulation. It is thermally protected against misuse of insulation materials and improper lamping. This air-tight housing design prevents airflow through ceiling for saving heating and air conditioning costs. The IC206AT offers a choice of trim types including baffle, reflector, lensed and eyeball trims.

HOUSING/MOUNTING FRAME:

6", new work, air-tight installation. Mounting frame of galvanized steel is 9 1/8" L x 6 7/8" W. The housing adjusts for ceilings up to 1 1/4" thick.

BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. The bar hangers can be turned 90° on the plaster frame. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

LAMPING/SOCKET:

90W Max., 120V (Lamp wattage based on trim). Adjustable socket with for consistent alignment of different trim and lamp types.

JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

COMPLIANCE:

UL, C-UL listed for damp location.
Certified Air-Tight under ATM-E283.

WARRANTY:

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

IC206AT


6" IC Type Housing for New Work Line Voltage



ORDERING INFORMATION

IC206AT

Sample Part Code: IC206ATQF



SERIES

IC206AT: IC Rated, Air Tight Housing,



OPTION

Q: 3 Quick Connectors,
QF: 3 Quick Connectors, and
Floating Socket

SPECIFICATIONS

