



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com



SPECIFICATION & FEATURES

Catalog Number
Notes
Job/Title

DESCRIPTION:

ICH304AT is a 4" aperture housing for one vertical halogen lamp, UL, C-UL listed for damp location. The ICH304AT is designed for insulated ceilings and can be in direct contact with insulation. It is thermally protected against misuse of insulation materials and improper lamping. This air-tight housing design prevents airflow through ceiling for saving heating and air conditioning costs. The ICH304AT offers a choice of trim types including baffle and reflector trims.

HOUSING/MOUNTING FRAME:

4", new work, air-tight installation. Mounting frame is made of galvanized steel is 12" L x 7 5/8" W. The housing adjusts for ceilings up to 1 1/4" thick.

BAR HANGERS:

Pre-installed bar hangers allow the housing to be positioned at any point within a 24" joist span. Bar hangers are designed to fit T-bar spine without additional clamps for use in a drop ceiling.

LAMPING/SOCKET:

50W Max., 120V GU10 base MR-16 (Lamp wattage based on trim). Adjustable socket mounting plate for proper positioning of different lamp types.

JUNCTION BOX:

J-box is listed for through-branch circuit wiring (5)11/16" knockouts, and (4) knockouts with Romex cable lamp. Ground wire is provided.

COMPLIANCE:

UL, C-UL listed for damp location.
Certified Air-Tight under ATM-E283

WARRANTY:


Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

ORDERING INFORMATION

ICH304AT

Sample Part Code: ICH304AT



SERIES

ICH304AT: IC Rated, Air Tight New Work Housing

ICH304AT

4" IC Type Housing for New Work Line Voltage



DIMENSIONS DATA

