



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

Catalog #:	08/21/2015
Project:	Type:
Prepared By:	

DESCRIPTION

The INDI industrial series is suitable for general purpose lighting in a wide variety of environments. The heavy duty design and low profile make this fixture a great fit for any commercial, industrial, retail or warehouse lighting applications.

HOUSING

- Hot-dipped galvanized steel housing - provides strength and durability
- Painted After Fabrication (PAF) - safe handling and added corrosion resistance
- Specially designed back reflector - enhanced lighting performance
- End caps can be used to join strips from end to end for continuous row mounting
- Numerous knockouts for easy installation

ELECTRICAL DETAILS

- NEC required ballast disconnect pre-installed

LISTINGS/RATINGS/COMPLIANCE

Fixtures are UL listed and suitable for damp locations.

WARRANTY

Guaranteed one year from the purchase date of the product, against mechanical defects in manufacturing.

NOTES


Product performance may vary depending on model and end user environment.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE ***




SPECIFICATIONS / DIMENSIONS


1 LAMP



2 LAMP



3 LAMP



DIMENSIONS

	L	W	H
4'	48"	11 1/4"	4"
8'	96"	11 1/4"	4"

ORDERING INFORMATION

Sample Part Code: INDI2454D

INDI SERIES	LAMP QTY	LENGTH	LAMP WATTAGE	D VOLTAGE	BALLAST OPTION
INDI	[1] : 1 Lamp [2] : 2 Lamp [3] : 3-4ft Lamps [4] : 4 x 4 ft Lamp (4: = 8 ft. Tandem) [6] : 6-4ft Lamps (8ft Tandem only)	[4] : 4ft [8] : 8ft 8 FT HAS (2) 4FT WHITE REFLECTORS	[28] : 28W T8 [28] : 28W T5 [32] : 32W T8 [44] : 44W T8HO [54] : 54W T5HO [60] : 60W T12HO [59] : 59W T8 8FT [86] : 86W T8HO 8FT [110] : 110W T12HO 8FT	[D] : 120-277V	[K] : 120-277V (2 ballast) [PS] : 120-277V Program Rapid Start [-DIM] : 120-277V 0-10V Series Elec. Dimming [-LPF] : 0.77 Low Ballast Factor 120-277V [-HPF] : 1.18 High Ballast Factor 120-277V [B1] : Emerg. 500 Lum. 1 Lamp [B2] : Emerg. 1400 Lum. 1 Lamp [B3] : Emerg. 1400 Lum. 2 Lamp