



TAMLITE LIGHTING

660 NW Peacock Blvd. Port St. Lucie, FL 34986
tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

HOUSING

Die cast aluminum housing with a durable textured bronze powdercoat finish. Housing has a removeable rear panel for driver access.

LENS

Clear tempered flat glass lens

MOUNTING

Unit is available with a wide yoke mount for mounting on flat surfaces, or a 1/2" adjustable knuckle for groundstake or box mounting. Yoke mount model comes with a 6' SJTW UL cord without plug. Knuckle mount model comes with 6" wire leads.

LIGHT OUTPUT PERFORMANCE

TOTAL LUMENS : 2200
LUMENS PER WATT : 75
COLOR TEMP. : 5000K
CRI : 80
DISTRIBUTION : TYPE II CUTOFF
LIFE : 50000 Hrs

ELECTRICAL DETAILS

INPUT WATTAGE : 30W
INPUT VOLTAGE : 120-277V
FREQUENCY : 50/60 Hz
POWER FACTOR : .90
MIN START TEMP : -30 DEGREES C

WARRANTY

Guaranteed for 5 years against mechanical defects in manufacturing.

Catalog #:	04/03/2017
Project:	Type:
Prepared By:	

RBFLLED Series

LED 30W COB Flood



SPECIFICATIONS / DIMENSIONS

Width: 8 5/8" Height: 6" Length: 4 1/2"

LISTINGS/RATINGS/COMPLIANCE

UL Listed wet locations

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

ORDERING INFORMATION

Sample Part Code: RBFLLED305KY

RBFLLED	30	5K	
SERIES	WATTAGE	COLOR TEMP	MOUNTING
RBFLLED	[30] : 30W	[5K] : 5000K	[Y] : Yoke