

CONTRACTOR:		
PROJECT:	DATE:	
PREPARED BY:	MODEL#: TRR56SQRF	

SERIES SPECIFICATIONS



TRR56SQRF

5/6", Square LED Retrofit

These LED Retrofit Kits are compatible with most 5" and 6" recessed cans. The TRR56SQRF is designed with a white baffle construction, and dimmable LED driver rated for 50,000 hours. Comes with 2 torsion clips. Suitable for IC and Non-IC housings.



PHYSICAL SPECIFICATIONS

Housing Material: Plastic

Ambient Temperature: -20° C (-4° F) - $+40^{\circ}$ C ($+104^{\circ}$ F)


Lens/ Optic Material: Polycarbonate


Color: White


Mounting Type: Recessed housing


Dimming Type: Triac

LINE DRAWING









Dimming Percentage: 10%-100%





CONTRACTOR:		
PROJECT:	DATE:	
PREPARED BY:	MODEL#: TRR56SQRF	

ORDERING INFORMATION

EXAMPLE: TRR56SQRF-3

SERIES	SIZE	STYLE	ТҮРЕ	COLOR TEMP.
TRR [56]:5/6″	[SQ]: Square	[RF]:Retrofit	[-3]: 3000K	
			[-4]:4000K	
			[-5]:5000K	

TECHNICAL SPECS

Input Voltage	120V
Input Power	13W
Lumens	900lm (3000K)
Color Temperature	3000К, 40000К, 5000К
Operating temperature	From -20° to $+40^{\circ}$
Frequency	60 Hz
CRI	90
LED Lifespan	50,000 HRS
Dimmable	10-100%*