

TAMLITE LIGHTING 660 NW Peacock Blvd. Port St. Lucie, FL 34986 tel: (772) 878-4944 or on the web at www.tamliteusa.com

SPECIFICATION & FEATURES

MOUNTING

HOR Pendant Mount

The pendant mount suspension option "PD" is available for 4, 6, 8 and 10 light variations. Factory installed 14 gauge steel mounting bracket and balanced ballast placement.

HOR Gripple

Gripple suspension hanging systems are a fast, adjustable and easy way to mount fixtures.

SENSOR

HOR Fixture Mount Occupancy Sensors

The HOR series occupancy sensor option features a Passive Infrared fixture mounted occupancy sensor that is designed simply to automatically turn lights on with and auto off timer.

For use in spaces where ceiling heights can vary from 8' to 40'; such as warehouses, manufacturing facilities, industrial area and all other high ceiling applications. It comes with three interchangeable lenses for use in a 360° high-bay general area or an aisle way. OS Sensor provides reliable coverage up to 40' mounting heights.

*** SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE***

Catalog #:	08/13/2015
Project:	Type:
Prepared By:	

HOR Series Fluorescent High Bay Accessories





SPECIFICATIONS / DIMENSIONS

Width Height
14 Watts Dimensions: 11.81 Inches 3.54 Inches
25 Watts Dimensions: 16.15 Inches 4.06 Inches

ORDERING INFORMATION

Sample Part Code: HOR



HOR