



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

DESCRIPTION



TRRRT RGBW 24v

The TRRRT16KIT includes everything needed to bring RGBW color options to any job or installation. The RGBW, color changing, ribbon tape will allow you to create an ever changing ambiance to suit any mood desired. This kit includes an RF remote and receiver that makes changing colors, setting levels, and creating color shifts easy and fun. The 16' spool can be cut & spliced every 4 inches on clearly marked cut points to create custom lengths for your installation needs. Splice connectors included will allow you to add angles and jump gaps.



FEATURES AND WARRANTY

Intended Use

Residential, commercial, under cabinets, show cases, cove lighting.

Location Rating

Indoor use

Max Run Length

32ft

Dimmable

Dimmable with controller

Cuttible Length

Every 4"

Warranty

1-year limited warranty

ORDERING INFORMATION

EXAMPLE: TRRRT16RKIT-RGBNW

SERIES	16 FT REELS	COLOR TEMP	LOCATION
TRRRT16RKIT	[-RGB]: COLOR CHANGE	[WW]: 3000K [NW]: 4000K	[BLANK]: DRY IP20

DIMENSIONS

SERIES	L	W	H
TRRRT16KIT-RGBWW	16'	0.5"	0.0625"
TRRRT16R-RGBWW	16'	0.5"	0.0625"
TRRRT16KIT-RGBNW	16'	0.5"	0.0625"
TRRRT16R-RGBNW	16'	0.5"	0.0625"

APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

LIGHTING SPECIFICATIONS

SERIES	WHITE LUMENS	LPW	WATTAGE	VOLTAGE	CRI
TRRRT16KIT-RGBWW	67	27.91	2.4W/FT	24V	90
TRRRT16R-RGBWW	67	27.91	2.4W/FT	24V	90
TRRRT16KIT-RGBNW	67	27.91	2.4W/FT	24V	90
TRRRT16R-RGBNW	67	27.91	2.4W/FT	24V	90

PERFORMANCE SPECIFICATIONS

TRRRT70WDRIVER IN KIT

ELECTRICAL SPECIFICATIONS	
Nominal W	72W
Input	
Input Voltage (VAC)	120V-240V (+/- 10%)
Frequency Range (Hz)	50-60 Hz (+/- 5%)
Power Factor @ Full Load	>0.9
Output	
Output Voltage (VDC)	24v

ACCESSORIES

TRRRT KITS include the following items:*

- 1x TRRRT70DRIVER
- 2x TRRRT2SC**
- 1x TRRRT8FTSC**
- 1x TRRRT-RF

*See Accessories sheet below for details and additional accessory information.
**TRRRT- WET KITS include -WET IP65 connectors.



TRRRT2SC (Included)
0549-5760
2" SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRRT6SC
0549-5763
6" SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRRT12SC
0549-5769
12" SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL#:

ACCESSORIES



TRRR24SC
0549-5772
24" SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRR4FTSC
0549-5775
4FT SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRR8FTSC (Included)
0549-5778
8FT SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRRBSC-WET
0549-5826
BUTT SPLICE CONN 5 PIN
Voltage rating
12~36V



TRRR2-WAY
0549-5784
2 WAY SPLICE CONN CBL 5 PIN
Voltage rating
12~36V



TRRR70DWT
0549-5790
70W DIMMABLE DRIVER FOR TRRRT RG
Voltage rating
24V



TRRR70WDRIVER (Included)
0549-5787
70W 24V DRIVER FOR TRRRT RGBW SERIES
Voltage rating
24V



TRRR-BT
0549-5796
BLUE TOOTH RECEIVER/REMOTE FOR TRRRT SERIES
Voltage rating
12~36V



TRRR-RF (Included)
0549-5805
RF RECEIVER AND REMOTE FOR TRRRT SERIES
Voltage rating
12~36V



TRRRT-ALEXA CONTROL
0549-5799
ALEXA CONTROL FOR TRRRT SERIES
Voltage rating
12~36V

APPLICATION AND PERFORMANCE SPECIFICATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION